

Coolant Exchanger



- Exchange and Backflush Cooling System in less than 10 minutes.
- Two line approach allows coolant transfer up to 1 gallon per minute.
- Quick and easy to use.
- Includes heat resistant delrin adapters and tools.



Visit www.aecgroup.net for video of the Coolant Exchanger

Coolant Exchanger



3 Tube Model - CE3000+

Specifications:

- 8" rigid wheels (rear)
- 3 1/2" swivel casters with brakes (front)
- 8" steel reinforced external hoses

Features:

- Quick and easy hook up
- Two lines, pressure and vacuum, for coolant exchange up to 1 gal. per minute
- Large 4.25 U.S. gallon capacity
- Easily accessible cylinders for filling
- Balanced, stable design
- CAD designed
- Shut off valve on radiator adapter
- Delrin (non heat conductive) adapters
- Durable, high quality components
- One year limited warranty



Vacuum: 26 Hg (minimum)
 Pressure: Factory set to 10 PSI
 Air requirement: 70 PSI, +/- 6 CFM
 Weight: 90 lbs. (41 kgs.)
 Shipping weight: 100 pounds (45.4 kgs.)
 Dimensions: 20.0" wide (50.8 cm)
 19.0" deep (48.3 cm)
 47.0" high (119 cm)



AEC GROUP INC. 3600 W. Carriage Drive, Santa Ana, CA 92704
 Toll-Free: 877-906-1395 • Phone: 714-444-1395 • Fax: 714-444-1396 • www.aecgroup.net